

Premium Galvanized Window Wells



Safety Covers Available







Well made. Well protected.

Add more light and air into sub-grade windows with AIL's Premium Galvanized Window Wells — quality made for added performance and safety.

- Lightweight and strong
- ► Heavy-duty, corrosion-resistant, galvanized steel
- ► Flanges for better sealing
- ▶ Rolled top edge for added strength and safety
- Available in egress sizes
- Easy to install
- ► Optional Safety Covers available





Well covered.

Safety Covers offer fall-protection for children, adults, pets and wildlife, while minimizing leaves and debris in the well.

- ► Gravity fit, easy to remove
- Corrosion-resistant, galvanized steel
- ► Heavy-duty welded grating with rolled angle frame
- Available in all sizes

When sizing your Window Well

The inside width measurement of the Window Well should be at least 4–6" wider than the window opening. The Well height should be enough to extend 4–6" above the soil grade and at least 8" below the bottom of the window opening. The Projection is the measurement from front to back. Egress sizing is required for below–grade bedroom windows.

1						
WINDOW WELLS				SAFETY COVERS		
INSIDE WIDTH	PROJECTION	HEIGHT	AIL PART NUMBER	INSIDE WIDTH	PROJECTION	AIL PART NUMBER
36"	12"	12"	WWF080900300300	- 36"	12"	WWF0900300CV
		22"	WWF080900300550			
42"	12"	22"	WWF081060300550	- 42"	12"	WWF1060300CV
		36"	WWF081060300900			
49"	22"	22"	WWF081240550550	49"	22"	WWF1240550CV
54"	22"	22"	WWF101370550550	- 54"	22"	WWF1370550CV
		36"	WWF101370550900			
62"	22"	22"	WWF101570550550	62"	22"	WWF1570550CV
EGRESS WINDOW WELLS*				EGRESS SAFETY COVERS*		
49"	30"	22"	WWF081240760550	49"	30"	WWF1240760CV
54"	30"	22"	WWF101370760550	- 54"	30"	WWF1370760CV
		36"	WWF101370760900			
62"	30"	22"	WWF101570760550	62"	30"	WWF1570760CV

* Conforms to building codes for basement bedroom windows. Sizing information is a guideline only. Please check your local building codes to ensure code compliance for egress window wells.



640 Waydom Drive Ayr, Ontario NOB 1E0 1-519-622-8600